

La Méthode

MTC-PTP

Moins de temps à coder, plus de temps à la plage

REMI CORSON

Automattic
@remicorson
remicorson.com



Jeux d'roles

Deñmo

What the Grunt?

Grunt est un
tasks runner

Cake - Gulp - Broccoli

Grunt est basé sur

Nojje.jis

Node.js permet
d'utiliser JavaScript
en dehors du navigateur

Installer Node.js

<https://nodejs.org/>

NPM

Node Package Manager

Installer Grunt

```
$ npm init // puis plusieurs fois entrée
```

```
$ npm install -g grunt-cli
```

```
$ npm install grunt --save-dev // dans le projet
```

Test de l'install Grunt

```
$ grunt --help
```


Usage

```
grunt [options] [task [task ...]]
```

Options

```
--help, -h      Display this help text.
--base          Specify an alternate base path. By default, all file paths are
                relative to the Gruntfile. (grunt.file.setBase) *
--no-color      Disable colored output.
--gruntfile     Specify an alternate Gruntfile. By default, grunt looks in the
                current or parent directories for the nearest Gruntfile.js or
                Gruntfile.coffee file.
--debug, -d     Enable debugging mode for tasks that support it.
--stack        Print a stack trace when exiting with a warning or fatal error.
--force, -f     A way to force your way past warnings. Want a suggestion? Don't
                use this option, fix your code.
--tasks        Additional directory paths to scan for task and "extra" files.
                (grunt.loadTasks) *
--npm          Npm-installed grunt plugins to scan for task and "extra" files.
                (grunt.loadNpmTasks) *
--no-write      Disable writing files (dry run).
--verbose, -v   Verbose mode. A lot more information output.
--version, -V   Print the grunt version. Combine with --verbose for more info.
--completion    Output shell auto-completion rules. See the grunt-cli
                documentation for more information.
```

Grunt-init

Project Scaffolding

```
npm install -g grunt-init
```


Test de l'install Grunt-init

```
$ grunt --help
```

```
MBP-de-Remi:~ remi$ grunt-init --help
```

```
grunt-init: Generate project scaffolding from a template. (v0.3.2)
```

Usage

```
grunt-init [options] [template]
```

Options

```
--help, -h      Display this help text.
--no-color      Disable colored output.
--debug, -d     Enable debugging mode for tasks that support it.
  --stack      Print a stack trace when exiting with a warning or fatal error.
--force, -f     A way to force your way past warnings. Want a suggestion? Don't
                use this option, fix your code.
  --no-write    Disable writing files (dry run).
--verbose, -v   Verbose mode. A lot more information output.
--version, -V   Print the grunt version. Combine with --verbose for more info.
```

Available templates

```
wp-cpt  Create a commonjs module, including Nodeunit unit tests.
wp-plugin  Create a WordPress plugin.
wp-theme  Create a WordPress theme.
```

Templates that exist in the `/Users/remi/.grunt-init` directory may be run with `"grunt-init TEMPLATE"`. Templates that exist in another location may be run with `"grunt-init /path/to/TEMPLATE"`. A template is a directory that must contain, at

Créer un template

Le dossier du template se trouve sur macOS

`~/ .grunt-init/`

ou sur Windows

`%USERPROFILE%\ .grunt-init\`

Structure d'un template













3 Fichiers













`my-template/template.js`





`my-template/renome.json`

`my-template/root/`

root/

-  .gitignore
-  .gruntjshintrc
-  **assets** ▶
-  Gruntfile.js
-  **includes** ▶
-  **languages** ▶
-  package.json
-  plugin.php
-  README.md
-  README.txt
-  **templates** ▶
-  uninstall.php

-  .gitignore
-  .gruntjshintrc
-  assets
-  Gruntfile.js
-  **includes**
-  languages
-  package.json
-  plugin.php
-  README.md
-  README.txt
-  templates
-  uninstall.php

-  class-meta-boxes.php
-  class-post-types.php
-  class-taxonomies.php
-  class-template-functions.php

template.js

Avant de commencer

```
// Basic template description
exports.description = 'Create a WordPress plugin.';

// Template-specific notes to be displayed before question prompts.
exports.notes = '';

// Template-specific notes to be displayed after the question prompts.
exports.after = '';

// Any existing file or directory matching this wildcard will cause a warning.
exports.warnOn = '*';
```

Définir le projet

```
// The actual init template
exports.template = function( grunt, init, done ) {
  init.process( {}, [
    // Prompt for these values.
    init.prompt( 'title', 'My Book Store' ),
    init.prompt( 'description', 'A small plugin to do things better with WordPress!' ),
    init.prompt( 'plugin_uri', 'https://remicorson.com' ),
    init.prompt( 'author_name' ),
    init.prompt( 'author_email', 'remicorson@nospam.com' ),
    init.prompt( 'author_url', 'https://remicorson.com' ),
    ...
  ] );
}
```

Poser une question

```
{  
  name: 'custom_post_type',  
  message: 'WordPress CPT : enter the CPT name (ex: Book. Leave empty if no need for CPT)'  
},
```



```
{  
  name: 'taxonomy',  
  message: 'WordPress Taxonomy : enter the taxonomy name (ex: Style. Leave empty if no need for taxonomy)'  
}
```

Valeur par défaut 1

```
{  
  name: 'css_type',  
  message: 'CSS Preprocessor: Will you use "Sass", "LESS", or "none" for CSS with this project?',  
  default: 'Sass'  
},
```

Valeur par défaut 2

```
{  
  name: 'enable_templates',  
  message: 'Enable CPT templating (y/n)?',  
  default: 'yes'  
},
```

Dépendances

```
], function( err, props ) {  
  props.keywords = [];  
  props.version = '0.1.0';  
  props.devDependencies = {  
    "grunt": "^0.4.5",  
    "grunt-checktextdomain": "^1.0.1",  
    "grunt-contrib-clean": "^0.5.0",  
    "grunt-contrib-compress": "^0.8.0",  
    "grunt-contrib-copy": "^1.0.0",  
    "dp-grunt-contrib-copy": "^0.4.4",  
    "grunt-contrib-cssmin": "^1.0.2",  
    "grunt-contrib-uglify": "^2.0.0",  
    "grunt-contrib-watch": "^1.0.0",  
    "grunt-text-replace": "^0.4.0",  
    "grunt-wp-i18n": "^0.5.4"  
  };  
};
```

Préparer des variables

```
// Sanitize names where we need to for PHP/JS
props.name = props.title.replace( /\s+/g, '-' ).toLowerCase();

// Development prefix (i.e. to prefix PHP function names, variables)
props.prefix = props.prefix.replace( '/[^a-z_]/i', '' ).toLowerCase();

// Development prefix in all caps (e.g. for constants)
props.prefix_caps = props.prefix.toUpperCase();

// An additional value, safe to use as a JavaScript identifier.
props.safe_filename = props.name.replace( /[\W_]+/g, '-' ).replace( /^(\\d)/, '-$1' );
```

Copier des fichiers

```
var files = init.filesToCopy( props );
```

Copies conditionnelles 1

```
// Post Type Class
if( props.custom_post_type === '' ) {
    delete files[ 'includes/class-post-types.php' ];

    props.custom_post_type = '';
}
```

Copies conditionnelles 2

```
switch( props.css_type.toLowerCase()[0] ) {
  case 'l': // Use Less, delete Sass related files.
    delete files[ 'assets/css/style.scss' ];
    delete files[ 'assets/css/admin/style.scss' ];

    props.devDependencies["grunt-contrib-less"] = "~1.4.0";
    props.css_type = 'less';
    break;
  case 'n': // Use none, delete Sass and Less related files.
  case undefined:
    delete files[ 'assets/css/style.less' ];
    delete files[ 'assets/css/style.scss' ];
    delete files[ 'assets/css/admin/style.less' ];
    delete files[ 'assets/css/admin/style.scss' ];

    props.css_type = 'none';
    break;
  default: // Use Less files.
    delete files[ 'assets/css/style.less' ];
    delete files[ 'assets/css/admin/style.less' ];

    props.devDependencies["grunt-contrib-sass"] = "~1.0.0";
    props.css_type = 'sass';
    break;
}
```


Theming

```
// Template Class
switch( props.enable_templates ) {
    case 'no':
        delete files[ 'includes/class-template-loader.php' ];
        delete files[ 'templates/archive-.php' ];
        delete files[ 'templates/content-.php' ];
        delete files[ 'templates/' ];

        props.enable_templates = 'no';
        break;
}
```

Do the Magic!

```
// Actually copy and process files
init.copyAndProcess( files, props );

// Generate package.json file
init.writePackageJSON( 'package.json', props );

// Done!
done();
});
};
```

rename.js

Renommer à la volée

```
{  
  "plugin.php": "{%= js_safe_name %}.php",  
  "templates/archive-cpt.php": "templates/archive-{%= custom_post_type.toLowerCase() %}.php",  
  "templates/content-cpt.php": "templates/content-{%= custom_post_type.toLowerCase() %}.php",  
  "includes/class-meta-boxes.php": "includes/class-{%= safe_filename %}-meta-boxes.php",  
  "includes/class-post-types.php": "includes/class-{%= safe_filename %}-post-types.php",  
  "includes/class-taxonomies.php": "includes/class-{%= safe_filename %}-taxonomies.php",  
  "includes/class-template-functions.php": "includes/class-{%= safe_filename %}-template-functions.php",  
  "languages/plugin.pot": "languages/{%= safe_filename %}.pot"  
}
```

Recodage Party!

Readme.txt

=== {%= title %} ===

Contributors: {%= author_name %}

Donate link: {%= author_url %}

Tags:

Requires at least:

Tested up to:

Stable tag: 1.0.0

{%= description %}

plugin.php

```
/**
 * Plugin Name: {%= title %}
 * Plugin URI: {%= plugin_uri %}
 * Description: {%= description %}
 * Version: 1.0.0
 * Author: {%= author_name %}, Remi Corson
 * Contributors: {%= author_name %}, Remi Corson
 * Author URI: {%= author_url %}
 * Text Domain: {%= title.replace( /\s+/g, '_' ).toLowerCase() %}
 * Domain Path: /languages
```



```
if ( ! class_exists( '{%= _.capitalize(title.replace( /\s+/g, '-' )) %}' ) ) :  
  
    /**  
     * Main {%= _.capitalize(title.replace( /\s+/g, '-' )) %} class.  
     */  
    class {%= _.capitalize(title.replace( /\s+/g, '-' )) %} {
```

```
// Define constants.  
define( '%= title.replace( /\s+/g, "_" ).toUpperCase() %}_VERSION', '1.0.0' );
```

```
// Includes.  
{% if ( custom_post_type != '' ) { %}include_once( 'includes/class-{@= safe_filename }-post-types.php' );{% } %}  
{% if ( custom_post_type != '' ) { %}include_once( 'includes/class-{@= safe_filename }-meta-boxes.php' );{% } %}  
{% if ( enable_templates == 'yes' ) { %}include_once( 'includes/class-{@= safe_filename }-template-functions.php' );{% } %}  
{% if ( taxonomy != '' ) { %}include_once( 'includes/class-{@= safe_filename }-taxonomies.php' );{% } %}
```

Gruntfile.js

Compiler le CSS

```
// Compile all .scss files.
sass: {
  compile: {
    options: {
      sourcemap: 'none'
    },
    files: [{
      expand: true,
      cwd: '<%= dirs.css %>/',
      src: ['*.scss'],
      dest: '<%= dirs.css %>/',
      ext: '.css'
    }]
  }
},
```

Minifier le CSS

```
// Minify all .css files.
cssmin: {
  minify: {
    expand: true,
    cwd: '<%= dirs.css %>/',
    src: ['*.css'],
    dest: '<%= dirs.css %>/',
    ext: '.css'
  }
},
```

Minifier le JS

```
// Minify .js files.
uglify: {
  options: {
    preserveComments: 'some'
  },
  jsfiles: {
    files: [{
      expand: true,
      cwd: '<%= dirs.js %>/',
      src: [
        '*.js',
        '!*.min.js',
        '!Gruntfile.js',
      ],
      dest: '<%= dirs.js %>/',
      ext: '.min.js'
    }]
  }
},
```


Watch

```
// Watch changes for assets
watch: {
  css: {
    files: ['<%= dirs.css %>/*.scss'],
    tasks: ['sass', 'cssmin'],
  },
  js: {
    files: [
      '<%= dirs.js %>/*.js',
      '!<%= dirs.js %>/*.min.js'
    ],
    tasks: ['uglify']
  }
},
```

Make Pot

```
// Create .pot files
makepot: {
  dist: {
    options: {
      domainPath: '/languages/',
      exclude: [
        'node_modules/.*',
        'build/*.*'
      ],
      potFilename: 'js_safe_name.pot',
      type: 'wp-plugin',
      potHeaders: {
        'language': 'en',
        'plural-forms': 'nplurals=2; plural=(n != 1);',
        'x-poedit-country': 'United States',
        'x-poedit-sourcecharset': 'UTF-8',
        'x-poedit-keywordlist': '__;_e;__gettext:1,2;_n:1,2;__gettext_noop:1,2;_n_noop:1,2;_c;_nc:1,2;_x:1,2c;_ex:1,2c;_nx:4c,1,2;_nx_noop:4c,1,2;',
        'x-poedit-basepath': '../',
        'x-poedit-searchpath-0': '.',
        'x-poedit-bookmarks': '',
        'x-textdomain-support': 'yes',
        'report-msgid-bugs-to': 'https://remicorson.com',
        'language-team': 'YOUR TEAM <YOUR-EMAIL@ADDRESS>'
      }
    }
  }
},
```

clean

```
// Clean up build directory  
clean: {  
    main: ['build/<%= pkg.name %>']  
},
```

copy dans build/

```
// Copy into the build directory
copy: {
  main: {
    expand: true,
    src: [
      '**',
      '!node_modules/**',
      '!build/**',
      '!.sass-cache/**',
      '!Gruntfile.js',
      '!package.json',
      '!**/Gruntfile.js',
      '!**/package.json',
      '!<%= dirs.css %>/*.scss',
      '!**/*~'
    ],
    dest: 'build/<%= pkg.name %>/',
  },
},
```

zip

```
//Compress build directory into <name>.zip and <name>-<version>.zip
compress: {
  main: {
    options: {
      mode: 'zip',
      archive: './build/<%= pkg.name %>-<%= pkg.version %>.zip'
    },
    expand: true,
    cwd: 'build/<%= pkg.name %>',
    src: ['**/*'],
    dest: '<%= pkg.name %>'
  }
},
```

Modules

```
// Load NPM tasks to be used here
grunt.loadNpmTasks( 'grunt-wp-i18n' );
grunt.loadNpmTasks( 'grunt-contrib-sass' );
grunt.loadNpmTasks( 'grunt-contrib-cssmin' );
grunt.loadNpmTasks( 'grunt-contrib-uglify' );
grunt.loadNpmTasks( 'grunt-contrib-watch' );
grunt.loadNpmTasks( 'grunt-checktextdomain' );
grunt.loadNpmTasks( 'grunt-contrib-clean' );
grunt.loadNpmTasks( 'grunt-contrib-copy' );
grunt.loadNpmTasks( 'grunt-contrib-compress' );
```

Register Tasks

```
// Register tasks
grunt.registerTask( 'default', [
  'sass',
  'cssmin',
  'uglify'
] );

// Just an alias for pot file generation
grunt.registerTask( 'pot', [
  'makepot'
] );

// Build task(s).
grunt.registerTask( 'build', [
  'clean',
  'copy',
  'compress',
  'build-clean'
] );

// Build-clean task(s).
grunt.registerTask( 'build-clean', [
  'clean'
] );
```

BOODOM!